

Ropex RES-203 - Resistron RES-403 Upgrade In-stock USA
 Force Global, Inc. | e-mail info@forceglobal.com
 ph: 414 507-9378 | fx: 262-628-4451

RESISTRON

TEMPERATURE CONTROLLER
 FOR HEATSEAL BANDS
 TO SEAL PLASTIC FILMS

RES-203

FEATURES

- ★ Compact in size with easy DIN rail mounting for inside the control cabinet.
- ★ Self monitoring with "Alarm Signal" and "Alarm Signal" output.
- ★ Alternate remote start signal, 24 VDC or closed hard contact.
- ★ Analogue temperature output signal, 0-10 VDC, to indicate actual temperature.
- ★ Snap on terminal connectors for convenient hook-up.
- ★ High reliability, hybrid technology.
- ★ Jumper for easy selection of frequency 50/60 Hz.
- ★ Easy installation and operation.
- ★ Cost effective - Improved production, less scrap.



TABLE OF CONTENTS

1. INTRODUCTION	6. OPERATING MODES
2. PRINCIPLE OF OPERATION	6.1 Constant heat
3. FUNCTIONS	6.2 Impulse mode
3.1 Control Function	6.2.1 Timing of impulse
3.2 Alarm Function	6.3 LED Output
3.2.1 Alarm Signal	6.4 Current Diagram
3.2.2 Reset	
3.3 Zero calibration	7. HEATSEAL ELEMENT
3.4 Temperature Setting	8. TECHNICAL SPECIFICATIONS
3.5 Temperature output signal (actual temperature)	9. INSTALLATION DRAWINGS
3.6 Start function	10. ACCESSORIES
4. WIRING DIAGRAM	11. GENERAL INSTALLATION GUIDELINES
5. OPERATING INSTRUCTIONS	